


RPT1002H THIN FILM PLATINUM RTD ELEMENT

- * 100 ohms at 0°C
- * 3850 ppm/K Temp. Coefficient of Resistance
- * Temperature Range -70°C to +600°C
- * Excellent high temperature stability
- * Designed for large quantity applications



STI PART NUMBER	DIN CLASS
RPT1002HA1	A
RPT1002HB1	B

DIMENSIONS	(mm)
x	1.90
y	2.30
t	1.0
L	8.0
d	0.20

(°C)	Resistance (Ω)	DIN Class A		DIN Class B	
		± °C	± Ω	± °C	± Ω
-50	80.31	0.25	0.10	0.55	0.22
-25	90.19	0.20	0.08	0.43	0.17
0	100.00	0.15	0.06	0.30	0.12
25	109.74	0.20	0.08	0.43	0.13
50	119.40	0.25	0.10	0.55	0.21
75	128.99	0.30	0.11	0.68	0.26
100	138.51	0.35	0.13	0.80	0.30
125	147.95	0.40	0.15	0.93	0.35
150	157.33	0.45	0.17	1.05	0.39
175	166.63	0.50	0.19	1.18	0.44
200	175.86	0.55	0.20	1.30	0.48
225	185.01	0.60	0.22	1.43	0.52
250	194.10	0.65	0.24	1.55	0.56
275	203.11	0.70	0.25	1.68	0.60
300	212.05	0.75	0.27	1.80	0.64
325	220.92	0.80	0.28	1.93	0.68
350	229.72	0.85	0.30	2.05	0.72
375	238.44	0.90	0.31	2.18	0.76
400	247.09	0.95	0.33	2.30	0.79
425	255.67	1.00	0.34	2.43	0.83
450	264.18	1.05	0.36	2.55	0.86
475	272.61	1.10	0.37	2.68	0.90
500	280.98	1.15	0.38	2.80	0.93

* Lead wire material is platinum clad palladium
Suitable for welding, crimping or brazing

* Suggested measuring current:
0.1 mA to 1.0 mA to prevent self-heating

* Operating temperature range (continuous):

DIN Class B: -70°C to +600°C

DIN Class A: -50°C to +300°C

** This table available in other temperature ranges and increments.

Sensing Technologies, Inc.
5582 Enterprise Parkway
Fort Myers, FL 33905
TEL 239-600- 6633
FAX 239-694-0031

Sensing Technologies, Inc.
1028 Graphite Road
St. Marys, PA 15857
TEL: 814-834-9480
FAX: 814-834-1556

For engineering assistance, contact
jsidoni@sensing-tech.com